



SPECS

TECNOLOGIA IBRIDA	
MOTORE	Giant SyncDrive Sport
DISPLAY	Giant RideControl Plus
BATTERIA	Giant EnergyPak Smart 625, 36V Integrated Lithium-Ion
TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Desert Sage
TELAIO	ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
FORCELLA	RockShox Recon Silver RL, 130mm travel, Lockout, 110x15mm Boost, Maxle Stealth, e-MTB optimized
AMMORTIZZATORE	RockShox Monarch RT, High Volume, 184x44mm, custom tuned
COMPONENTISTICA	
MANUBRIO	Giant Connect TR Riser 31.8x780mm
ATTACCO MANUBRIO	Giant Contact
TUBOSELLA	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/L&XL:170)
SELLA	Giant Sport
PEDALI	Aluminum Platform
SISTEMA DI TRASMISSIONE	
LEVE DEL CAMBIO	SRAM SX Eagle 12-speed
DERAGLIATORE	MRP 1X CS custom
CAMBIO	SRAM SX Eagle 12-speed
FRENI	Shimano MT420, 4-piston, hydraulic disc, 203mm
COMANDI FRENO	Shimano MT401
PACCO PIGNONI	SRAM PG-1210, 11-50T, 12-Speed
CATENA	SRAM SX Eagle PowerLock, 12-speed
GUARNITURA	SRAM X-Sync Eagle 38T 104BCD chainring Forged Alloy minimal Q-factor, (S:160, M/L:165, XL:170)
DROP MOVIMENTO CENTRALE	N/A
RUOTE	
CERCHI	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
MOZZI	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR
RAGGI	Stainless Steel
COPERTURE	Maxxis Rekon 29x2.4" foldable, 60tpi, EXO, Tubeless Ready
EXTRA	Giant EnergyPak 6A Smart charger

CARATTERISTICHE

- Telaio: ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
- Forcella: RockShox Recon Silver RL, 130mm travel, Lockout, 110x15mm Boost, Maxle Stealth, e-MTB optimized
- Leve del cambio: SRAM SX Eagle 12-speed
- Guarnitura: SRAM X-Sync Eagle 38T 104BCD chainring Forged Alloy minimal Q-factor, (S:160, M/L:165, XL:170)
- Colorazioni: Desert Sage

Prezzo: € 3.849,00

GEOMETRIA

TELAIO	S	M	L	XL
Lunghezza tubo sella (mm)	406	432	482	507
Angolo tubo sella	73,5°	73,5°	73,5°	73,5°
Lunghezza tubo orizzontale (mm)	580	600	625	650
Lunghezza tubo sterzo (mm)	100	110	120	135
Angolo sterzo	67,0°	67,0°	67,0°	67,0°
Rake forcella (mm)	40	40	40	40
Trail (mm)	113,6	113,6	113,6	113,6
Interasse (mm)	1166	1187	1213	1240
Lunghezza carro posteriore (mm)	475	475	475	475
Drop movimento centrale (mm)	20	20	20	20
Stack (mm)	593	603	612	626
Reach (mm)	404	421	444	465
Altezza stand over (mm)	741	756	788	792
Larghezza manubrio c/c (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	40	40	50	50
Lunghezza pedivella (mm)	160	160	165	165
Dimensione ruote	29"	29"	29"	29"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.